

**DX55**  
55KG  
120LB

**DX77**  
77KG  
170LB

**DX90**  
90KG  
200LB

# Primus DX Range

## Tumble Dryer



### KEY FEATURES

- Controls:
  - Dual Digital Control or OPL Micro
- Gas, Steam heating, Electrical heating (DX55)
- Large door opening for easy loading and unloading (Ø 68cm)
- Galvanized drum
- Radial airflow
- Standard reversing drum
- Self-cleaning lint screen
- Preheating of intake air

### OPTIONS

- Stainless steel drum
- Stainless steel front panel with black painted door
- Residual moisture control Sensodry+®:
  - lower energy and utility costs
  - lower linen replacement costs
- SafeTech™ Fire Suppression System



FAST DRYING



LOW ENERGY  
CONSUMPTION



LARGE DOOR  
OPENING

# WOLF

0800 840 9598  
[www.wolflaundry.co.uk](http://www.wolflaundry.co.uk)

# PRIMUS DX RANGE

TYPE		DX55	DX77	DX90
<b>CAPACITY</b>				
Maximum capacity	kg (lb)	55 (120)	77 (170)	90 (200)
Volume	litres	1020	1410	1660
Diameter	mm	1120	1290	1290
<b>AIRFLOW</b>	l/s	660	1010	1010
<b>DRYING AVERAGE</b>				
Gas heating	g/min	979	1401	1673
Electrical heating	g/min	698	-	-
<b>MOTORS</b>				
Fan	kW	1.1	1.1	1.1
Drive	kW	1.1	1.1	1.1
<b>GAS HEATING</b>				
Gas connection	NPT	1"	1"	1"
Electrical connection		3x 200-240V/50-60Hz, 3x 440-480V/50-60Hz, 3x 380-415V/50-60Hz		
Energy	kW	79	116	125
	kBTU/h	270	395	425
<b>STEAM HEATING</b>				
Steam connection	NPT	3/4"		
Electrical connection		3x200-240V/50-60Hz, 3x440-480V/50-60Hz, 3x380-415V/50-60Hz		
High pressure 6.9 bar	kW	54.95	77.81	77.81
	kBTU/h	187.5	265.5	265.5
<b>ELECTRICAL HEATING</b>				
Electrical connection		3x230-240V/50-60Hz 3x380V/50-60Hz 3x400-415V/50-60Hz 3x440V/50-60Hz 3x460-480V/50-60Hz	-	-
Energy	kW	60	-	-
<b>EXHAUST</b>	mm	Ø 254	Ø 305	Ø 305
<b>DIMENSIONS</b>				
HxWxD	mm	2175x1170x1270	2390x1345x1315	2390x1345x1505
Net weight (G,S)	kg	565, 555, 605	-, 635, 705	-, 705, 770
<b>TRANSPORT DATA</b>				
Packed (foil E, G) HxWxD	mm	2290x1220x1820	2510x1320x1870	2510x1320x2070
Gross weight (foil, E, G,S)	kg	600, 585, 635	-, 670, 740	-, 740, 805
Packed (crate) HxWxD	mm	2310x1350x1890	2550x1530x1950	2550x1530x2140
Gross weight (crate, E, G, S)	kg	675, 660, 710	-, 755, 825	-, 825, 895

