

TA 9340
VENTED
8KG

TC 9350
CONDENSER
8KG

TW 9360
HEAT PUMP
8KG

Schulthess topLine Pro Drying Range

Swissmade Commercial Tumble Dryers




KEY FEATURES

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left
- Anthracite or chrome steel finish

OPTIONS

- Exhaust air system (TA 9340)
- Condensation system (TC 9350)
- Condensation system with heat pump (TW 9360)
- Anthracite or chrome steel finish



Minimised space requirements

Thanks to their compact design, topLine Pro machines are exceptionally economical on space. With the stacking kit, washers and dryers can be placed on top of each other in just 0.5 square meters of space.



At the touch of a button

A total of 10 special programmes are now available for fabric-specific laundry care at the touch of a button. The language selection button gives you a choice of up to 17 languages ranging from English and Spanish to Polish and Russian, with direct selection.

SCHULTHESS TOPLINE PRO RANGE

Company or brand name		Schulthess	Schulthess	Schulthess
Type of appliance		Exhaust air dryer	Condensation dryer with heat-exchanger air	Condensation dryer with heat pump
Type or sales description		topLine pro TA 9340	topLine pro TC 9350	topLine pro TW 9360
Product number		9340.1U	9350.1U	9360.1U
Load capacity	max. kg	8	8	8
Structural design				
Stand-alone unit with work surface		•	•	•
Standard unit for washing and drying tower		•	•	•
Door hinge ³⁾		r / l / w	r / l / w	r / l / w
Dimensions ⁴⁾				
Height	cm	90	90	90
Width	cm	63	63	63
Depth including space from wall	cm	83	84	84
Height for built-in installation	cm	90,5	90,5	90,5
Depth with door open	cm	144	146	146
Height (adjustable)	cm	2	2	2
Drying control				
By time selection ⁵⁾		•	•	•
Automatic by electronic moisture detection ⁶⁾		•	•	•
System and Equipment				
Drying technology		Air extraction system	Air condensation system	Condensation system with heat pump
Programme time display		•	•	•
Automatic door opening		•	•	•
Loading opening	cm	front, x 36 / 31 / 180°	front, x 36 / 31 / 180°	front, x 36 / 31 / 180°
LED drum lighting		•	•	•
Connecting cable	m	1,5	1,5	1,5
Outlet hose	m	-	2 / x 22 mm	2 / x 22 mm
Condensate drainage in container / Drainage direct		-	•	•
Exhaust air duct		x 100 mm, 90°-angle adapter	-	-
Maximum drain height	m	-	1	1
Exhaust hose x 100 mm	m	2	-	-
Power supply - Electrical connection ⁷⁾				
Voltage	V	400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 3N~ / 400 V 2N~ / 230 V 1N~	400 V 2N~
Connected values	kW	5,9 / 4,4 / 2,2	5,1 / 3,7 / 2,3	3,4
Fuse protection	A	10 / 10 / 10	10 / 10 / 10	10
Safety and service				
Conforms to the European Machinery Directive		2006/42/EC	2006/42/EC	2006/42/EC
Country of origin		Switzerland	Switzerland	Switzerland
Guarantee ⁸⁾		1 year	1 year	1 year

Explanations:

• Available or yes - Not available or no

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

4) The stated dimensions are minimum dimensions for the niche where the machine is built in.

Further dimensions can be found in the dimension sheets.

5) Set the degree of drying according to the laundry items, as shown in the operating instructions.

6) Degree of drying is maintained automatically.

7) Information on switchover options can be found in the installation instructions, where required.

8) Outside Switzerland: 1 year

WOLF

0800 840 9598
www.wolflaundry.co.uk