

Schulthess baseLine Range

Swissmade Compact Laundry Equipment

WASHING MACHINE

Schulthess baseLine 7720



Load capacity: 1 – 7 kg
Spin speed: 1500 – 200 rpm

Equipment

- Large 4.3" colour display
- Drum vanes for 3D-Washing
- LED drum lighting
- Drum capacity: 60 l
- Spin speed: 1500 rpm
- g Factor 605
- Residual moisture 44%
- With drain valve or drain pump
- Language selection button (23 languages)
- profiClean programme button
- Favorites for your 6 favourite programmes
- Programme progress and remaining time display
- Door opening angle 180°
- Door hinge right or left

Programmes

- 35 profiClean programmes for small commercial businesses, building cleaners and special programmes
- 24 freely programmable slots
- 40–85 °C disinfection programmes
- Programme groups Sportswear, Businesswear, Homecare, Antibac

Safety systems

- Control display for water intake / drainage
- Imbalance sensor / child lock / foam level monitoring

Options

- Hot water connection
- Programme expansion module with PC interface
- Coin box interface
- Machine plinth in chrome steel, H: 35.5 cm
- Machine plinth with fluff filter drawer, H: 40 cm

TUMBLE DRYER

Schulthess baseLine TC 7730



Load capacity: 1 – 7 kg

Equipment

- Condensation dryer
- Large 4.3" colour display
- Stainless steel drum
- LED drum lighting
- Drum capacity: 118 l
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Excellent noise insulation
- Crease protection
- Programme progress and remaining time display
- Door opening angle 180°
- Door hinge right or left

Programmes

- Automatic programs with 5 drying levels from mangle moist to extra-dry.
- Time-controlled drying programmes 10–150 minutes
- Gentle drying at reduced temperature
- 7 kg of laundry is cabinet dry in 83 min. (cotton, 1600 rpm)

Safety systems

- Temperature monitoring
- Child lock / condensed water drainage monitoring Options
- Stacking kit for washer-dryer tower
- Coin box interface
- Machine plinth in chrome steel, H: 35,5 cm

baseLine Washing Machine

Company or brand name		Schulthess
Type of appliance		Washing machine
Type or sales description		baseLine 7720
Product number		
Model with drain pump (P)		7720.1PU
Model with drain valve (V)		7720.1UV
Application features		
Load capacity	max. kg	7
Drum capacity	l	60
Spinning speed	max. rpm	1500
g Factor	g	605
Residual moisture 1)	%	44
Structural design		
Footed appliance with work surface		•
Door hinge 3)		r/l/w
Dimensions		
Height	cm	85
Width	cm	60
Depth including distance from wall	cm	67
Depth with door open (front loader)	cm	110
Height (adjustable)	cm	1
Weight when empty	kg	90
Equipment		
Detergent tank and drum		chrome-nickel steel
Loading opening	cm	34 / 180°
Automatic door opening		•
Connecting cable	m	1.6
Drain:		
- Drain hose with benda, only model (P)	m	1.5
- Model with drain pump (P)	mm	21
- Model with drain valve (V)	mm	50
Electric power and water supply		
Electrical connection		400 V 2N~ / 50Hz / 4.6kW 10A
Voltage / connected loads /fuse		230 V 1 N~ / 50Hz / 2.3kW 10A
Water connection		
- Pressure hose G ¾" with fine filter	m	1.5
- Can be connected to cold water hot water		cold water/ hot water 70 °C
- Water pressure	bar	1-10
Options		
		- Door hinge left
		- Hot water connection
		- Drum lighting
		- Drain valve or drain pump
		- RFID-Card-System
		- Connection for 8 liquid detergents with dosing pump
		- Machine plinth
		- Machine plinth with drawer for fluff filter
Safety and service		
Conforms to the European Machinery Directive		2006/42/EC
Country of origin		Switzerland
Guarantee		1 year
Service by		Schulthess Maschinen AG

baseLine Tumble Dryer

Company or brand name		Schulthess
Type of appliance		Condensation dryer with heat-exchanger air
Type or sales description		baseLine 7730
Product number		7730.1U
Load capacity	max. kg	7
Structural form		
Footed appliance with work surface		•
Standard unit for wash and dry column		•
Door hinge 3)		r / l / w
Dimensions		
Height	cm	85
Width	cm	60
Depth including distance from wall	cm	64
Height for built-in installation	cm	85.5
Depth with door open	cm	122
Height adjustable	cm	2
Drying control		
By time selection 5)		•
Automatic by electronic moisture detection 6)		•
System and equipment		
Drying technology		Air condensation system
Programme time display		•
Load quantity display		•
Automatic door opening		•
Loading opening	cm	vorne, x 36 / 31 / 180°
LED drum lighting		•
Connecting cable	m	1.5
Outlet hose	m	2 / x 22 mm
Condensate drainage in container / Drainage direct		•
Exhaust line		-
Maximum drainage height	m	1
Exhaust hose x 100 mm	m	-
Power supply		
Electrical connection 7)		
Voltage	V	400 V 2N~ / 230 V 1N~
Connected values	kW	2,8 / 2,1
Fuse protection	AT	10 / 10
		- Machine plinth
		- Machine plinth with drawer for fluff filter
Safety and service		
Conforms to the European Machinery Directive		2006/42/EC
Country of origin		Switzerland
Guarantee		1 year
Service by		Schulthess Maschinen AG
Name and address of supplier		Schulthess Maschinen AG CH-8633 Wolfhausen/ZH